



**L&T Switchgear\***  
**Business**

IS NOW



Electrical & Automation



Infrastructure



Home



Buildings



Agriculture



Industries

**Maximum Retail Prices**  
**For Final Distribution Products**  
Effective from 01-02-2025

**EXORA**

# FROM THE COO'S DESK.



**L&T Switchgear\*** IS NOW  
**Business**



**Electrical & Automation**

Dear Stakeholder,

We are pleased to announce the launch of our new brand "Lauritz Knudsen Electrical & Automation" on 29th May 2024 which will replace the existing brand, L&T Switchgear.

We sincerely thank you for your patronage & support over the last seven decades. We eagerly anticipate continuing this journey under the new name.

During this transition, the specific product names shall remain unchanged, such as ACBs - OMEGA & C-POWER, MCCB-DSine, Final Distribution Products (MCBs, RCCB, RCBO) – AU / Exora, Contactors -MNX/MO/MCX, Drives, PLCs, Metering products etc. Our products now feature a refreshed look that reflects our brand image and brings more consistency across our product line. However, please note that this change will not affect the ordering CAT numbers, technical parameters, and dimensions of our product range. Once the old brand material is exhausted, we will exclusively supply products under our new brand identity.

We assure you that this brand transition will be seamless, ensuring continuous availability of the products, including spares and after-sales support throughout the product's life cycle, whether under the L&T Switchgear or Lauritz Knudsen brand. Product warranties, as per our standard terms, will be honoured for products in both brands.

We kindly request you to update our new brand, Lauritz Knudsen Electrical & Automation, in your list of approved makes.

Thank you for your continued support and cooperation.

Best regards,

Naresh Kumar,




COO & Sr, VP, Electrical Standard Products

Lauritz Knudsen Electrical & Automation



## LK Electrical & Automation Lauritz Knudsen Final Distribution Products

Lauritz Knudsen's range of modular devices offer MCB, RCCB, Isolator & DB for final distribution of electrical power. Lauritz Knudsen's products are better known for reliability, functionality & ease of use.



## Lauritz Knudsen Final Distribution Products spell world class

Lauritz Knudsen products conform to relevant global standards viz. IEC, EN. They also have BIS, CE marking, CB and KEMA certification.

## Contents

MCB - Miniature Circuit Breaker	2
Isolators	6
RCCB - Residual Current Circuit Breaker	7
Other Protection & Control Devices	9
Industrial Plugs & Sockets	11
Distribution Boards	12



### Note:

[Grey colour : HSN code]

Current GST 18%, subject to changes as per Govt. notification




## E&A EXORA Final Distribution Products - the assurance of absolute safety



### Safety re-defined

Finger proof terminals eliminate chances of accidental contact with live part. You can install, operate and maintain modular device with total confidence.



### Energy limiting class - 3

If fault occurs, the Rapid Arc Quenching mechanism in modular device operates and extinguishes the arc quickly (within 3-5 msec), ensuring lowest possible energy flow through the circuit. This minimize risk of fire and maximizes life of your equipment.

### Safety meets superior aesthetics

Ergonomically designed, profiled for superior cooling and manufactured with fire retardant material. Modular device is brought to you keeping in mind utmost user safety.

## Key Benefits



### True contact indication

E&A modular device range enhances safety through true contact indication even from a distance regardless of its mounting and knob position. Red and Green indication tags provided below the knob positively identify the electrical ON/OFF status, reflecting actual contact status.



### Integrated label holder

E&A MCBs are equipped with label holder for easy identification of circuit during operation as well as in maintenance.




### Innovatively profiled breathing channels

When two or more poles are placed adjacent to each other, the breathing channels are so profiled that the air circulates around individual pole, resulting in cooler operation.



### Large terminal size and Biconnect

Exora MCB's can easily accommodate cables of up to 35 sq.mm. Biconnect terminals offer convenience of connecting both cable and bus bar.



### Two position DIN rail clip

Installation on a DIN rail is further simplified with a two-position DIN rail clip as a standard feature. E&A MCB range makes mounting on a standard DIN rail more convenient .



### Non-welding contacts

Silver Graphite contact tips ensure higher life and maximum safety against contact welding due to its superior anti-welding properties, enhancing safety and life of the system.



### Combihead screw

E&A modular devices with combihead screws, allow you to use standard as well as Philips head screw drivers. E&A modular device range addresses your undefined needs.



## Miniature Circuit Breaker (MCB) [8536]

### Range Highlights

- › True contact indication for individual pole
- › Label holder facility for all configurations
- › Conforms to IS/IEC 60898 - 10kA
- › Conforms to IEC 60947 - 2
  - › 15kA C-curve till 40 A
  - › 10kA C-curve for 50A, 63A
- › Available in B, C & D curves
- › Low watt loss - almost 50% of the values prescribed by IS/IEC 60898
- › Trip free mechanism
- › Design based on advanced current limiting hammer trip mechanism
- › No Line-Load bias
- › Bi connect feature on both sides
- › Suitable for accessory fitment



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>							
0.5A	1	-	-	BB10E50C	480	BB10E50D	485
1A	1	-	-	BB10010C	480	BB10010D	485
2A	1	-	-	BB10020C	480	BB10020D	485
3A	1	-	-	BB10030C	480	BB10030D	485
4A	1	-	-	BB10040C	480	BB10040D	485
6A	1	BB10060B	294	BB10060C	294	BB10060D	405
10A	1	BB10100B	294	BB10100C	294	BB10100D	405
16A	1	BB10160B	294	BB10160C	294	BB10160D	405
20A	1	BB10200B	294	BB10200C	294	BB10200D	405
25A	1	BB10250B	294	BB10250C	294	BB10250D	405
32A	1	BB10320B	294	BB10320C	294	BB10320D	405
40A	1	BB10400B	675	BB10400C	675	BB10400D	730
50A	1	BB10500B	675	BB10500C	675	BB10500D*	730
63A	1	BB10630B	675	BB10630C	675	BB10630D*	730
<b>Double Pole (DP)</b>							
0.5A	2	-	-	BB20E50C	1355	BB20E50D	1375
1A	2	-	-	BB20010C	1355	BB20010D	1375
2A	2	-	-	BB20020C	1355	BB20020D	1375
3A	2	-	-	BB20030C	1355	BB20030D	1375
4A	2	-	-	BB20040C	1355	BB20040D	1375
6A	2	BB20060B	970	BB20060C	970	BB20060D	1000
10A	2	BB20100B	970	BB20100C	970	BB20100D	1000
16A	2	BB20160B	970	BB20160C	970	BB20160D	1000
20A	2	BB20200B	970	BB20200C	970	BB20200D	1000
25A	2	BB20250B	970	BB20250C	970	BB20250D	1000
32A	2	BB20320B	970	BB20320C	970	BB20320D	1000
40A	2	BB20400B	1565	BB20400C	1565	BB20400D	1635
50A	2	BB20500B	1565	BB20500C	1565	BB20500D*	1635
63A	2	BB20630B	1565	BB20630C	1565	BB20630D*	1635
<b>Three Pole (TP)</b>							
0.5A	3	-	-	BB30E50C	1970	BB30E50D	2000
1A	3	-	-	BB30010C	1970	BB30010D	2000
2A	3	-	-	BB30020C	1970	BB30020D	2000
3A	3	-	-	BB30030C	1970	BB30030D	2000
4A	3	-	-	BB30040C	1970	BB30040D	2000
6A	3	BB30060B	1530	BB30060C	1530	BB30060D	1595
10A	3	BB30100B	1530	BB30100C	1530	BB30100D	1595
16A	3	BB30160B	1530	BB30160C	1530	BB30160D	1595
20A	3	BB30200B	1530	BB30200C	1530	BB30200D	1595
25A	3	BB30250B	1530	BB30250C	1530	BB30250D	1595
32A	3	BB30320B	1530	BB30320C	1530	BB30320D	1595
40A	3	BB30400B	2360	BB30400C	2360	BB30400D	2470
50A	3	BB30500B	2360	BB30500C	2360	BB30500D*	2470
63A	3	BB30630B	2360	BB30630C	2360	BB30630D*	2470

**Note:** Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

\*For details, please contact nearest branch office

## Miniature Circuit Breaker (MCB) [8536]



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Four Pole (FP)</b>							
0.5A	4	-	-	BB40E50C	2480	BB40E50D	2485
1A	4	-	-	BB40010C	2480	BB40010D	2485
2A	4	-	-	BB40020C	2480	BB40020D	2485
3A	4	-	-	BB40030C	2480	BB40030D	2485
4A	4	-	-	BB40040C	2480	BB40040D	2485
6A	4	BB40060B	2095	BB40060C	2095	BB40060D	2150
10A	4	BB40100B	2095	BB40100C	2095	BB40100D	2150
16A	4	BB40160B	2095	BB40160C	2095	BB40160D	2150
20A	4	BB40200B	2095	BB40200C	2095	BB40200D	2150
25A	4	BB40250B	2095	BB40250C	2095	BB40250D	2150
32A	4	BB40320B	2095	BB40320C	2095	BB40320D	2150
40A	4	BB40400B	2970	BB40400C	2970	BB40400D	3185
50A	4	BB40500B	2970	BB40500C	2970	BB40500D*	3185
63A	4	BB40630B	2970	BB40630C	2970	BB40630D*	3185

**Note:** Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

\*For details, please contact nearest branch office

## MCBs (Miniature Circuit Breakers) : 80A-125A [8536]

### Range Highlights

- › Short circuit Breaking Capacity - 15kA (IEC 60947-2, EN 60947-2)
- › C & D Characteristics
- › Available in SP, DP, TP and FP
- › Suitable for Isolation
- › Protection Degree - IP 20
- › Availability of wide Range of Site Mountable Accessories



Rating	Modules 1 Mod = 17.5 mm	C Curve Cat. No.	M.R.P. (₹) Per Unit	D Curve Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>					
80A	1.5	AU15S10803C	2710	AU15S10803D	3085
100A	1.5	AU15S11003C	3035	AU15S11003D	3450
125A	1.5	AU15S11253C	3265	AU15S11253D	3730
<b>Double Pole (DP)</b>					
80A	3	AU15S20803C	6005	AU15S20803D	6835
100A	3	AU15S21003C	6405	AU15S21003D	7285
125A	3	AU15S21253C	7050	AU15S21253D	8015
<b>Three Pole (TP)</b>					
80A	4.5	AU15S30803C	9475	AU15S30803D	10790
100A	4.5	AU15S31003C	10105	AU15S31003D	11485
125A	4.5	AU15S31253C	11210	AU15S31253D	12740
<b>Four Pole (FP)</b>					
80A	6	AU15S40803C	12375	AU15S40803D	14050
100A	6	AU15S41003C	12870	AU15S41003D	14645
125A	6	AU15S41253C	14575	AU15S41253D	16565

**CERTIFIED TO LEAD,  
TRUSTED FOR SAFETY.**

BIS-Certified HR MCBs Range - 80A, 100A & 125A



## Solar Combo MCBs [8536]

(AC MCB + DC MCB)



AC MCB<sup>^</sup> with C-Curve

Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
1 AC 16A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC221616	1805
<b>New</b> 1 AC 20A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC222020	1805
<b>New</b> 1 AC 20A DP MCB <sup>^</sup> + 1 DC 20A DP 500V MCB	2+2	SC222025	1805
1 AC 25A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC222516	1805
<b>New</b> 1 AC 25A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC222525	1805
1 AC 32A DP MCB <sup>^</sup> + 1 DC 16A DP 500V MCB	2+2	SC223216	1805
<b>New</b> 1 AC 32A DP MCB <sup>^</sup> + 1 DC 25A DP 500V MCB	2+2	SC223225	1805
1 AC 32A DP MCB <sup>^</sup> + 1 DC 32A DP 500V MCB	2+2	SC223232	1805

# Double the Protection, Twice the Power!

## Complete Protection for Solar Rooftop Installations

**DC MCB:**  
10kA as per IEC 60947-2

**AC MCB:**  
10kA as per IS/IEC 60898-1



## Miniature Circuit Breaker (MCB) [8536]

### DC MCBs as per IEC 60947-2 [8536]

Rated Voltage:  
Breaking capacity of 6 kA - BB Series DC MCBs

#### 130V DC SP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>			
0.5A	1	BB10E5DC	700
1A	1	BB1001DC	700
2A	1	BB1002DC	700
3A	1	BB1003DC	700
4A	1	BB1004DC	700
6A	1	BB1006DC	605
10A	1	BB1010DC	605
16A	1	BB1016DC	605
20A	1	BB1020DC	605
25A	1	BB1025DC	605
32A	1	BB1032DC	605
40A	1	BB1040DC	795
50A	1	BB1050DC	795
63A	1	BB1063DC	795



Rated Voltage:  
Breaking capacity of 10 kA - BJ Series DC MCBs

#### 250V DC SP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Single Pole (SP)</b>			
0.5A	1	BJ10E5DC	850
1A	1	BJ1001DC	850
2A	1	BJ1002DC	850
3A	1	BJ1003DC	850
4A	1	BJ1004DC	850
6A	1	BJ1006DC	695
10A	1	BJ1010DC	695
16A	1	BJ1016DC	695
20A	1	BJ1020DC	695
25A	1	BJ1025DC	695
32A	1	BJ1032DC	695
40A	1	BJ1040DC	960
50A	1	BJ1050DC	960
63A	1	BJ1063DC	960

**New**

#### 250V DC DP MCB

0.5A	2	BB20E5DC	1495
1A	2	BB2001DC	1495
2A	2	BB2002DC	1495
3A	2	BB2003DC	1495
4A	2	BB2004DC	1495
6A	2	BB2006DC	1315
10A	2	BB2010DC	1315
16A	2	BB2016DC	1315
20A	2	BB2020DC	1315
25A	2	BB2025DC	1315
32A	2	BB2032DC	1315
40A	2	BB2040DC	1780
50A	2	BB2050DC	1780
63A	2	BB2063DC	1780



#### 500V DC DP MCB

0.5A	2	BJ20E5DC	1775
1A	2	BJ2001DC	1775
2A	2	BJ2002DC	1775
3A	2	BJ2003DC	1775
4A	2	BJ2004DC	1775
6A	2	BJ2006DC	1500
10A	2	BJ2010DC	1500
16A	2	BJ2016DC	1500
20A	2	BJ2020DC	1500
25A	2	BJ2025DC	1500
32A	2	BJ2032DC	1500
40A	2	BJ2040DC	1910
50A	2	BJ2050DC	1910
63A	2	BJ2063DC	1910

**New**

Note: Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos.

### 1000V DC MCBs [8536]

Rated Voltage: 1000V DC  
with breaking capacity of 6 kA - BK Series DC MCBs

Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
DP 6A 1000V DC 6kA MCB	4	BK2006DC	2355
DP 10A 1000V DC 6kA MCB	4	BK2010DC	2355
DP 16A 1000V DC 6kA MCB	4	BK2016DC	2355
DP 20A 1000V DC 6kA MCB	4	BK2020DC	2355
DP 25A 1000V DC 6kA MCB	4	BK2025DC	2355
DP 32A 1000V DC 6kA MCB	4	BK2032DC	2355
DP 40A 1000V DC 6kA MCB	4	BK2040DC	2860
DP 50A 1000V DC 6kA MCB	4	BK2050DC	2860
DP 63A 1000V DC 6kA MCB	4	BK2063DC	2860

**New**





## Isolators [8536]



### Range Highlights

- › Conforms to IEC 60947-3
- › Utilization category AC-22A
- › Available in DP, TP and FP versions in 40A, 63A, 80A & 100A ratings

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole (DP)</b>			<b>Three Pole (TP)</b>			<b>Four Pole (FP)</b>			
40A	2	BF204000	590	3	BF304000	1030	4	BF404000	1330
63A	2	BF206300	760	3	BF306300	1200	4	BF406300	1390
80A	2	BF208000	970	3	BF308000	1315	4	BF408000	1560
100A	2	BF210000	1010	3	BF310000	1400	4	BF410000	1685

**Note:** Standard Pack Quantity for Isolator : DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

## RCCB (Residual Current Circuit Breaker) [8536]



### Range Highlights

- › Conforms to IS 12640 (Part 1) / IEC 61008-1
- › RCCBs are available in DP and FP versions from 25 to 100A ratings with 30 mA, 100 mA and 300mA sensitivity



- › Truly current operated - operation even at nominal Voltage
- › Operates on Core Balance Current Transformer (CBCT) principle
- › Advanced neutral mechanism

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole (DP)</b>				
25A	30 mA	2	BG202503	3315
	100 mA	2	BG202510	3445
	300 mA	2	BG202530	3445
40A	30 mA	2	BG204003	3720
	100 mA	2	BG204010	3940
	300 mA	2	BG204030	3940
63A	30 mA	2	BG206303	4640
	100 mA	2	BG206310	4755
	300 mA	2	BG206330	4755
100A	30 mA	2	BG210003	8100
	100 mA	2	BG210010	8200
	300 mA	2	BG210030	8200

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Four Pole (FP)</b>				
25A	30 mA	4	BG402503	4340
	100 mA	4	BG402510	4455
	300 mA	4	BG402530	4455
40A	30 mA	4	BG404003	4380
	100 mA	4	BG404010	4530
	300 mA	4	BG404030	4530
63A	30 mA	4	BG406303	4955
	100 mA	4	BG406310	5195
	300 mA	4	BG406330	5195
100A	30 mA	4	BG410003	8555
	100 mA	4	BG410010	8700
	300 mA	4	BG410030	8700

## RCCBs (Residual Current Circuit Breakers) : Type-Adi (with Added immunity) [8536]



### Range Highlights

- › Wide Range of Current Ratings - 25A to 100A
- › Precise Sensitivities for variety of applications - from 30mA to 300mA
- › 2P & 4P versions
- › Suitable for Isolation
- › Protection Degree - IP 20
- › Availability of wide Range of Site Mountable Accessories
- › Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P Adi</b>				
25A	30mA	2	AURAD202503	5385
	100mA	2	AURAD202510	5630
	300mA	2	AURAD202530	5630
40A	30mA	2	AURAD204003	5715
	100mA	2	AURAD204010	5805
	300mA	2	AURAD204030	5805
63A	30mA	2	AURAD206303	6685
	100mA	2	AURAD206310	6810
	300mA	2	AURAD206330	6810
100A	30mA	2	AURAD210003	9875

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>4P Adi</b>				
25A	30mA	4	AURAD402503	6510
	100mA	4	AURAD402510	6635
	300mA	4	AURAD402530	6635
40A	30mA	4	AURAD404003	6760
	100mA	4	AURAD404010	6865
	300mA	4	AURAD404030	6865
63A	30mA	4	AURAD406303	7360
	100mA	4	AURAD406310	7515
	300mA	4	AURAD406330	7515
100A	30mA	4	AURAD410003	11725
	300mA	4	AURAD410030	11725

# All-Rounder RCDs (RCCB & RCBO)

Specially designed Adi RCDs ensure Safe and Reliable protection for All Applications in AC networks with Pulsating DC along with Harmonics

Type A

AC

Harmonics



Added Immunity

# RCBOs (Residual Current Breaker with Overcurrent Protection) [8536]

## Range Highlights\*

- › Conforms to IEC 61009-1, IS 12640-2, EN 61009-1
- › Short circuit Breaking Capacity - 10kA
- › Precise Sensitivities for a variety of applications
  - › from 10mA to 300mA
- › Suitable for Isolation

## Type-AC

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P AC</b>				
6A	10mA	2	AUF3C200601	4980
	30mA	2	AUF3C200603	4980
	100mA	2	AUF3C200610	5085
	300mA	2	AUF3C200630	5145
10A	10mA	2	AUF3C201001	4980
	30mA	2	AUF3C201003	4980
	100mA	2	AUF3C201010	5085
	300mA	2	AUF3C201030	5145
16A	10mA	2	AUF3C201601	4980
	30mA	2	AUF3C201603	4980
	100mA	2	AUF3C201610	5085
	300mA	2	AUF3C201630	5145
20A	30mA	2	AUF3C202003	4980
	100mA	2	AUF3C202010	5085
	300mA	2	AUF3C202030	5145
25A	30mA	2	AUF3C202503	4980
	100mA	2	AUF3C202510	5085
	300mA	2	AUF3C202530	5145
32A	30mA	2	AUF3C203203	4980
	100mA	2	AUF3C203210	5085
	300mA	2	AUF3C203230	5145
40A	30mA	2	AUF3C204003	4980
	100mA	2	AUF3C204010	5085
	300mA	2	AUF3C204030	5145
63A	30mA	4	AUF3C206303	5940
	100mA	4	AUF3C206310	6300
	300mA	4	AUF3C206330	6350
<b>4P AC</b>				
16A	30mA	7.5	AUF3C401603	5370
	100mA	7.5	AUF3C401610	5980
	300mA	7.5	AUF3C401630	6100
20A	30mA	7.5	AUF3C402003	5370
	100mA	7.5	AUF3C402010	5980
	300mA	7.5	AUF3C402030	6100
25A	30mA	7.5	AUF3C402503	5370
	100mA	7.5	AUF3C402510	5980
	300mA	7.5	AUF3C402530	6100
32A	30mA	7.5	AUF3C403203	5545
	100mA	7.5	AUF3C403210	5985
	300mA	7.5	AUF3C403230	6115
40A	30mA	7.5	AUF3C404003	5635
	100mA	7.5	AUF3C404010	5985
	300mA	7.5	AUF3C404030	6135
63A	30mA	7.5	AUF3C406303	6750
	100mA	7.5	AUF3C406310	6875
	300mA	7.5	AUF3C406330	6875
80A	30mA	12	AUF3C408003	25685
	100mA	12	AUF3C408010	26260
	300mA	12	AUF3C408030	26260
100A	30mA	12	AUF3C410003	27460
	100mA	12	AUF3C410010	28115
	300mA	12	AUF3C410030	28115



- › Availability of wide Range of Site Mountable Accessories
- › Available in
  - › Type AC: For standard AC installations
  - › Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

## Type-Adi

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
<b>2P Adi</b>				
6A	30mA	2	AUF3D200603	6600
	100mA	2	AUF3D200610	7265
	300mA	2	AUF3D200630	7540
10A	30mA	2	AUF3D201003	6600
	100mA	2	AUF3D201010	7265
	300mA	2	AUF3D201030	7540
16A	30mA	2	AUF3D201603	6600
	100mA	2	AUF3D201610	7265
	300mA	2	AUF3D201630	7540
20A	30mA	2	AUF3D202003	6600
	100mA	2	AUF3D202010	7265
	300mA	2	AUF3D202030	7540
25A	30mA	2	AUF3D202503	6600
	100mA	2	AUF3D202510	7265
	300mA	2	AUF3D202530	7540
32A	30mA	2	AUF3D203203	6600
	100mA	2	AUF3D203210	7265
	300mA	2	AUF3D203230	7540
40A	30mA	2	AUF3D204003	6600
	100mA	2	AUF3D204010	7265
	300mA	2	AUF3D204030	7540
63A	30mA	4	AUF3D206303	7665
	100mA	4	AUF3D206310	8110
	300mA	4	AUF3D206330	8180
<b>4P Adi</b>				
16A	30mA	7.5	AUF3D401603	6925
	100mA	7.5	AUF3D401610	7705
	300mA	7.5	AUF3D401630	7860
20A	30mA	7.5	AUF3D402003	6925
	100mA	7.5	AUF3D402010	7705
	300mA	7.5	AUF3D402030	7860
25A	30mA	7.5	AUF3D402503	6925
	100mA	7.5	AUF3D402510	7705
	300mA	7.5	AUF3D402530	7860
32A	30mA	7.5	AUF3D403203	7150
	100mA	7.5	AUF3D403210	7710
	300mA	7.5	AUF3D403230	7870
40A	30mA	7.5	AUF3D404003	7255
	100mA	7.5	AUF3D404010	7710
	300mA	7.5	AUF3D404030	7905
63A	30mA	7.5	AUF3D406303	8695
	100mA	7.5	AUF3D406310	8870
	300mA	7.5	AUF3D406330	8870
80A	30mA	12	AUF3D408003	25685
	100mA	12	AUF3D408010	26260
	300mA	12	AUF3D408030	26260
100A	30mA	12	AUF3D410003	27460
	100mA	12	AUF3D410010	28115
	300mA	12	AUF3D410030	28115

\*For technical details, please contact nearest branch office

## SPDs (Surge Protection Devices) [8536]



### Range Highlights

- › Conforms to IEC 61643-11
- › Available in Type 2 and Type 1+2
- › Type 2 : Protection against indirect lightning and switching surges
  - » Maximum Discharge Current - I<sub>max</sub> up to 70kA
- › Type 1+2 : Protection against direct and indirect lightning surges
  - » Maximum Discharge Current - I<sub>max</sub> up to 100kA



### 440V Application (Common + Differential Mode)

Description	I <sub>max</sub>	Configuration	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Type 1+2, I <sub>imp</sub> 12.5kA	50kA	1P+N	2	AUSP121PN50D	10545
		3P+N	4	AUSP123PN50D	20195
Type 2	40kA	1P+N	1	AUSP021PN40D	6590
		3P+N	2	AUSP023PN40D	13170
Type 2	15kA	1P+N	1	AUSP021PN15D	5270
		3P+N	2	AUSP023PN15D	10370
Type 1+2, I <sub>imp</sub> 8kA	100kA	1P+N	2	AUSP121PN100D	9480
		3P+N	4	AUSP123PN100D	18625
Type 2	70kA	1P+N	2	AUSP021PN70D	10350
		3P+N	4	AUSP023PN70D	17240

Type 2	15kA	1P+N	1	AUSP021PN15*	5270
--------	------	------	---	--------------	------

\*Available till stocks last

## 800V Solar Application

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage (Uc)	Cat. No.	M.R.P. (₹) Per Unit
Type 2, I <sub>max</sub> 40kA	3P	4	1500	AUSP023P40-1500	12500
Type 1+2, I <sub>imp</sub> 12.5kA	3P	5	1360	AUSP123P50-1360	41430
Type 1+2, I <sub>imp</sub> 12.5kA	3P	4	880	AUSP123P50-880	30000

### SPD Cartridges

Description	Cat. No.	M.R.P. (₹) Per Unit
Cartridge for AUSP021PN15D	AUSC021PN15D	2640
Cartridge for AUSP021PN40D	AUSC021PN40D	3290
Cartridge for AUSP021PN70D / AUSP023PN70D	AUSC021PN70D	3520
Cartridge for AUSP023PN15D <sup>#</sup>	AUSC023PN15D	3455
Cartridge for AUSP023PN40D <sup>#</sup>	AUSC023PN40D	4395
Cartridge for AUSP121PN100D / AUSP123PN100D	AUSC121PN100D	5270
Cartridge for AUSP121PN50D / AUSP123PN50D	AUSC121PN50D	5690
Cartridge for AUSP023PN15D <sup>#</sup>	AUSC023PN15DG	4005
Cartridge for AUSP023PN40D <sup>#</sup>	AUSC023PN40DG	4180

<sup>#</sup>For technical details, please contact nearest branch office

## ACCL (Automatic Changeover with Current Limiter) [8536]

### Single Phase ACCL



### Range Highlights

- › Conforms to IEC 60947-6, IEC 60947-3
- › Wide Range of Current Ratings
  - » (Generator side) - 1A to 30A
  - » (Electricity Board side) - 30A
- › RoHS compliant

Description EB/DG	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
30A/1A	4	AUCL01030001	2505
30A/1.5A	4	AUCL010301E5	2505
30A/2A	4	AUCL01030002	2505
30A/2.5A	4	AUCL010302E5	2505
30A/3A	4	AUCL01030003	2505
30A/4A	4	AUCL01030004	2505
30A/5A	4	AUCL01030005	2505
30A/6A	4	AUCL01030006	2505
30A/8A	4	AUCL01030008	2505
30A/10A	4	AUCL01030010	2505
30A/12A	4	AUCL01030012	2505
30A/15A	4	AUCL01030015	2505
30A/20A	4	AUCL01030020	2505
30A/30A	4	AUCL01030030*	2505

\*Non-current limiting variant

### Changeover Switches [8536]

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Double Pole</b>			
25A	2	AUC00202500	1710
40A	2	AUC00204000	2615
63A	3	AUC00206300	3045

### Three Phase ACCL



### Range Highlights

- › Settable overload current limit at DG side
- › Separate power consumption monitoring for Mains & Genset
- › Settable overvoltage & undervoltage protection
- › Settable TPN or SPN mode at DG side
- › Protection against single phasing

Description (AC-1) EB/DG	Cat. No.	M.R.P. (₹) Per Unit
32A / 32A	AUCL03032032	11385
40A / 32A	AUCL03040032	11730
40A / 40A	AUCL03040040	12700
50A / 50A	AUCL03050050	18095
63A / 50A	AUCL03063050	19970
63A / 63A	AUCL03063063	22620
80A / 80A	AUCL03080080	34475
125A / 125A	AUCL03125125	58035

For 3 Phase ACCL programming video please scan the QR code or click here



### Range Highlights

- › Conforms to IEC 60947-3 and IS/IEC 60947-3
- › Available in 3 positions (I-O-II) with centre off position
- › Utilization category AC-22A



Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
<b>Four Pole</b>			
40A	4	AUC00404000	4505
63A	6	AUC00406300	5110

## Modular Contactors [8536]



### Range Highlights

- › Wide Range of Current Ratings:
  - » 25A, 40A and 63A
- › Conforms to :
  - » IEC 61095, EN 61095
  - » IEC 60947-4-1, EN 60947-4-1
  - » IEC 60947-5-1
- › Protection Degree IP 20

## Time Switches [9107]



Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Analog time switch	1	AUTS01ANA00*	5110
Analog time switch	3	AUTS03ANA00*	6215
Digital time switch	2	AUTS02DIG00*1	3955
Astro time switch	2	AUTS02AST00*1	6645
Digital time switch	2	67DDT0#	2430
Astro time switch	2	T2DDT7#	4635

\*Available till stocks last #Substitute products of 1 marked

## Accessories

### Accessories [8538]




All Half Module and One Module Accessories are common for 80A-125A MCBs, RCBOs and Adi RCCBs

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage	CAT Nos.	M.R.P. (₹) Per Unit
Auxiliary Contact	1NO+1NC	0.5	240V AC, 24V DC	AUAXAC240	1005
AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240	1180
HR AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240HR	1180
Undervoltage Release	-	1	240V AC	AUUVAC240	2380
Release	-	1	24V DC	AUUVDC024	2380
Oversvoltage Release	-	1	240V AC	AUOVAC240	2945
Shunt Release	-	1	240V AC	AUSRAC240	2730
	-	1	24V DC	AUSRDC024	2730
Padlock-Suitable for Lock Hasp 3.5 - 5 mm dia. max	Suitable for 1Pole=1Mod devices: RCCBs, RCBOs, Changeover Switches up to 40A			AUPD01	540
	Suitable for 1Pole-1.5Mod devices: MCBs 80A-125A, Changeover Switch 63A			AUPD02	610

**Note:** Standard Pack Quantity for Padlock - 2 Nos.

\*For 80A-125A MCBs please contact nearest branch office

### Auxiliary & Accessories for Exora MCBs [8538]



Description	Cat. No.	M.R.P. (₹) Per Unit
Auxiliary Contact - 6A, 240V AC, (1NO+1NC), 0.5 Mod	BZA11006	940
Shunt Release - 240V AC, 1 Mod	BZS00240	2570
Trip Alarm Contact - 6A, 240V AC, (1NO+1NC), 0.5 Mod	BZT11006	1100

Description (AC-1)	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
25A-1NO	1	AUMC1002501	1900
25A-2NO	1	AUMC2002501	2380
40A-2NO	3	AUMC2004003	4075
40A-3NO	3	AUMC3004003	5840
40A-4NO	3	AUMC4004003	6850
63A-2NO+2NC	3	AUMC2206303	7240
63A-3NO	3	AUMC3006303	7420
63A-4NO	3	AUMC4006303	8170
<b>Accessory [8538]</b>			
Auxiliary Contact, 2NO	0.5	AUMCAUX240	1825

## Energy Meters [9030]



### Range Highlights

- › DIN mounting whole current operated meter
- › Accuracy Class 1.0
- › Inbuilt RS485 option
- › **Parameters** : Voltage, Current, kW, kWh, kVA, kVAh, RPM, Load hours, Interruptions

Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Single Phase - 60A	2	WD4010100000	2895
Three Phase - 80A	5	WD4020100000	6275
Single Phase - 60A (RS485)	2	WD4010110000	4285
Three Phase - 80A (RS485)	5	WD4020110000	9465

## Indicating Lights [8531]



Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
RED	1	AUI01RED00	1105
YELLOW	1	AUI01YEL00	1105
BLUE	1	AUI01BLU00	1105
GREEN	1	AUI01GRE00	1105
RED-YELLOW-BLUE	1	AUI01RYB00	1345

## Plugs



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Plug - IP44</b>		
16A, 2P+E	PSKPM30164	610
32A, 2P+E	PSKPM30324	960
16A, 3P+E	PSKPM40164	780
32A, 3P+E	PSKPM40324	1135
16A, 3P+N+E	PSKPM50164	820
32A, 3P+N+E	PSKPM50324	1095
<b>Plug - IP67</b>		
16A, 2P + E	PSKPM30167	1355
32A, 2P + E	PSKPM30327	1915
63A, 2P + E	PSKPM30637	5435
16A, 3P + E	PSKPM40167	1530
32A, 3P + E	PSKPM40327	2420
63A, 3P + E	PSKPM40637	5175
16A, 3P + N + F	PSKPM50167	1640
32A, 3P + N + E	PSKPM50327	2085
63A, 3P + N + E	PSKPM50637	5185
125A, 3P + N + E	PSKPM51257	15840

## Socket Angled



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket Angled - IP44</b>		
16A, 2P+E	PSKSA30164	655
32A, 2P+E	PSKSA30324	1160
16A, 3P+E	PSKSA40164	990
32A, 3P+E	PSKSA40324	1370
16A, 3P+N+E	PSKSA50164	1055
32A, 3P+N+E	PSKSA50324	1340
<b>Socket Angled - IP67</b>		
16A, 2P+E	PSKSA30167	1250
32A, 2P+E	PSKSA30327	1630
63A, 2P+E	PSKSA30637	5340
32A, 3P+E	PSKSA40327	2420
63A, 3P+E	PSKSA40637	5350
32A, 3P+N+E	PSKSA50327	1930
63A, 3P+N+E	PSKSA50637	5455
125A, 3P+N+E	PSKSA51257	18105

## Socket



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket - IP44</b>		
16A, 2P+E	PSKSM30164	845
32A, 2P+E	PSKSM30324	1180
16A, 3P+E	PSKSM40164	990
16A, 3P + N + E	PSKSM50164	1080
32A, 3P + N + E	PSKSM50324	1445
<b>Socket - IP67</b>		
16A, 2P+E	PSKSM30167	1590
32A, 2P+E	PSKSM30327	2185
63A, 2P+E	PSKSM30637	5915
16A, 3P+E	PSKSM40167	1995
63A, 3P+E	PSKSM40637	5970
16A, 3P + N + E	PSKSM50167	2085
32A, 3P + N + E	PSKSM50327	2440
63A, 3P + N + E	PSKSM50637	6065
125A, 3P + N + E	PSKSM51257	19040

## Socket Straight



### Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
<b>Socket Straight- IP44</b>		
16A, 2P+E	PSKSS30164	750
32A, 2P+E	PSKSS30324	1190
32A, 3P+N+E	PSKSS50324	1490
<b>Socket Straight- IP67</b>		
16A, 2P+E	PSKSS30167	1260
63A, 2P+E	PSKSS30637	6465
63A, 3P+E	PSKSS40637	5400
63A, 3P+N+E	PSKSS50637	5400
125A, 3P+N+E	PSKSS51257	18105

*Specially Designed*

## Distribution Board suitable for Aluminum shuttering (Mivan) Construction



> To experience Scan or click



### DBs suitable for Aluminum Shuttering Construction [8537]

#### SPN DBs

##### Highlights

- > Available in CRCA sheet steel, RAL9003, powder coated
- > Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- > With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 43 - Metal Door</b>				
4 way	2	2	LTSD04M	*
6 way	2	4	LTSD06M	*
8 way	2	6	LTSD08M	*
12 way	2	10	LTSD12M	*
16 way	2	14	LTSD16M	*

#### TPN DBs

##### Highlights

- > Available in CRCA sheet steel, RAL 9003, powder coated
- > Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- > With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	LTTD04M	*
6 way	8	6+6+6	LTTD06M	*
8 way	8	8+8+8	LTTD08M	*

\* For details, please contact nearest branch office

# SAFETY IN EVERY DETAIL, WITH EXORA DISTRIBUTION BOARDS



## Key Features:

- Elegant Curved Door design for stylish touch.
- Ergonomically designed push latch for enhanced safety.
- Spacious interiors facilitating ease of wiring.
- Uniform gasketing ensures long lasting IP protection.
- Effective earthing via earthing Wire ensuring safety.
- Aluminium-Zinc coated hardware for rustproof longevity
- Inbuilt Copper Wire Set (16 sq mm) & Shorting links for safer connections.
- Customised solutions to meet specific customer requirements.

## Key Highlights:

IEC 61439 1 & 3  
IP 30, 43 & 54  
IK 08 & IK09



**Highlights**

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- › With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
<b>IP 30 - Single Door</b>				
4 way	2	2	DESPN004SDS	1625
6 way	2	4	DESPN006SDS	1705
8 way	2	6	DESPN008SDS	1965
12 way	2	10	DESPN012SDS	2330
16 way	2	14	DESPN016SDS	2855
18 way	2	16	DESPN018SDS	3320
<b>IP 43 - Metal Door</b>				
4 way	2	2	DESPN004DDS	2120
6 way	2	4	DESPN006DDS	2440
8 way	2	6	DESPN008DDS	2615
12 way	2	10	DESPN012DDS	3135
16 way	2	14	DESPN016DDS	3965
18 way	2	16	DESPN018DDS	4150
<b>IP 43 - Glazed Door</b>				
4 way	2	2	DESPN004GDS	2835
6 way	2	4	DESPN006GDS	3020
8 way	2	6	DESPN008GDS	3280
12 way	2	10	DESPN012GDS	3995
16 way	2	14	DESPN016GDS	4965
18 way	2	16	DESPN018GDS	5255
<b>IP 54 - Metal Door</b>				
4 way	2	2	DESPN00454S	7395
6 way	2	4	DESPN00654S	8245
8 way	2	6	DESPN00854S	8770
12 way	2	10	DESPN01254S	10070
16 way	2	14	DESPN01654S	11210
18 way	2	16	DESPN01854S	11460

**Highlights**

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SPMCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 30 - Single Door</b>				
4 way	4	4+4+4	DETPN004SDS	4235
6 way	4	6+6+6	DETPN006SDS	5200
4 way	8	4+4+4	DETPN004SDS	4465
6 way	8	6+6+6	DETPN006SDS	5525
8 way	8	8+8+8	DETPN008SDS	6520
12 way	8	12+12+12	DETPN012SDS	9390
16 way	8	16+16+16	DETPN016SDS	11450
<b>IP 43 - Metal Door</b>				
4 way	4	4+4+4	DETPN004DDS	4980
6 way	4	6+6+6	DETPN006DDS	6190
4 way	8	4+4+4	DETPN004DDS	5210
6 way	8	6+6+6	DETPN006DDS	6490
8 way	8	8+8+8	DETPN008DDS	7790
12 way	8	12+12+12	DETPN012DDS	11620
16 way	8	16+16+16	DETPN016DDS	14420
<b>IP 43 - Glazed Door</b>				
4 way	4	4+4+4	DETPN004GDS	6765
6 way	4	6+6+6	DETPN006GDS	8130
4 way	8	4+4+4	DETPN004GDS	7040
6 way	8	6+6+6	DETPN006GDS	8570
8 way	8	8+8+8	DETPN008GDS	10160
12 way	8	12+12+12	DETPN012GDS	15585
16 way	8	16+16+16	DETPN016GDS	18730
<b>IP 54 - Metal Door</b>				
4 way	4	4+4+4	DETPN00454S	16895
6 way	4	6+6+6	DETPN00654S	19745
4 way	8	4+4+4	DETPN00454S	17860
6 way	8	6+6+6	DETPN00654S	21505
8 way	8	8+8+8	DETPN00854S	23510
12 way	8	12+12+12	DETPN01254S	33135
16 way	8	16+16+16	DETPN01654S	39770

For ordering old DBs, replace Cat no with "DB" instead of "DE".  
 Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

**Highlights**

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB / Isolator / RCCB / RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



**Horizontal PPI DBs**

IP 43 - Metal Door

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	8	2+2+2	4+4+4	DEHPI004DD	9265
6 way	8	2+2+2	6+6+6	DEHPI006DD	10970
8 way	8	2+2+2	8+8+8	DEHPI008DD	13155
12 way	8	2+2+2	12+12+12	DEHPI012DD	18125
16 way	8	2+2+2	16+16+16	DEHPI016DD	21745



**Tier PPI DBs**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
6 way	8	2+2+2	6+6+6	DETPPI006DD	11350
8 way	8	2+2+2	8+8+8	DETPPI008DD	14230
10 way	8	2+2+2	10+10+10	DETPPI010DD	14920
12 way	8	2+2+2	12+12+12	DETPPI012DD	15805
16 way	8	2+2+2	16+16+16	DETPPI016DD	18020
12 way	MCCB*	2+2+2	12+12+12	DETPPL012DD	16905

\*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DNO-100D & DNO-100C MCCB as incomer

**Highlights**

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for
  - » Modular Incomer - FP MCB/Isolator/RCCB/RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing
  - » MCCB Incomer - MCCB\* as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



**With Modular Incomer**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	8	4+4+4	4+4+4	DEPSG004DD	13605
6 way	8	4+4+4	6+6+6	DEPSG006DD	15340
8 way	8	4+4+4	8+8+8	DEPSG008DD	17115
12 way	8	4+4+4	12+12+12	DEPSG012DD	21230



**With MCCB Incomer**

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Sub-Incomer	Outgoing		
<b>IP 43 - Metal Door</b>					
4 way	MCCB	4+4+4	4+4+4	DEPGL004DD	18715
6 way	MCCB	4+4+4	6+6+6	DEPGL006DD	21400
8 way	MCCB	4+4+4	8+8+8	DEPGL008DD	24750
12 way	MCCB	4+4+4	12+12+12	DEPGL012DD	27915

\*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DNO-100D & DNO-100C MCCB as incomer

## New TPN Phase Selector DB [8537]

### Highlights

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 3 nos. of 63A E&A rotary switches | 3 nos. of rocker switches for phase identification | 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for - FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	DEPSR004DD	16710
6 way	8	6+6+6	DEPSR006DD	16975
8 way	8	8+8+8	DEPSR008DD	18185
10 way	8	10+10+10	DEPSR010DD	19430
12 way	8	12+12+12	DEPSR012DD	20485

## New Flexi/Row DB [8537]

### Highlights

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | cable ties | circuit identification labels
- › With provision to mount modular devices as per requirement



Description	No. of Modules Per Row	Cat. Nos.	M.R.P. (₹) Per Unit
2 Row 28 Module	14	DEROW228DD	6630
3 Row 42 Module	14	DEROW342DD	7950
4 Row 56 Module	14	DEROW456DD	8645
4 Row 64 Module	16	DEROW464DD	10055

## New Vertical TPN DB with Modular Incomer [8537]

### Highlights

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP/ TP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	8	4+4+4	DEVTM004DD	12835
6 way	8	6+6+6	DEVTM006DD	14300
8 way	8	8+8+8	DEVTM008DD	16600
12 way	8	12+12+12	DEVTM012DD	22390
16 way	8	16+16+16	DEVTM016DD	26715
<b>IP 54 - Metal Door</b>				
4 way	8	4+4+4	DEVTM00454	27135
6 way	8	6+6+6	DEVTM00654	29605
8 way	8	8+8+8	DEVTM00854	32690

## New Vertical TPND B with MCCB Incomer [8537]

### Highlights

- › Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for 3 pole and 4 Pole MCCB\* as incomer and SP/TP MCBs as outgoing



### Up to 125A MCCB Incomer

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTL004DD	15180
6 way	MCCB	6+6+6	DEVTL006DD	17255
8 way	MCCB	8+8+8	DEVTL008DD	18995
12 way	MCCB	12+12+12	DEVTL012DD	25840
16 way	MCCB	16+16+16	DEVTL016DD	30825
<b>IP 54 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTL00454	31445
6 way	MCCB	6+6+6	DEVTL00654	35860
8 way	MCCB	8+8+8	DEVTL00854	38820

\*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DU125D, DU125H & DNO MCCB as incomer

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eq. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

**New** Vertical TPN DB with MCCB Incomer [8537]

**Up to 250A MCCB Incomer**




Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
<b>IP 43 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTH004DD	19725
6 way	MCCB	6+6+6	DEVTH006DD	22090
8 way	MCCB	8+8+8	DEVTH008DD	24295
12 way	MCCB	12+12+12	DEVTH012DD	29405
16 way	MCCB	16+16+16	DEVTH016DD	39515
<b>IP 54 - Metal Door</b>				
4 way	MCCB	4+4+4	DEVTH00454	36090
6 way	MCCB	6+6+6	DEVTH00654	39405
8 way	MCCB	8+8+8	DEVTH00854	40755

\*Suitable for 3 pole and 4 pole DU250, DU250C & DN1 MCCB as incomer

**New** Enclosure [8537]

**Highlights**

- > Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- > Suitable for Surface and Flush mounting
- > Available in CRCA sheet steel, RAL9003, powder coated
- > With provision to mount MCB/Isolator/RCCB/RCBO and other modular devices



**IP 30 - Metal Door**

Description	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
<b>IP 30 - Metal Door</b>			
2 way	2	DEENC002SD	825
3 way	3	DEENC003SD	825
4 way	4	DEENC004SD	825
6 way	6	DEENC006SD	1280

**New** Plug & Socket DB [8537]

**Highlights**

- > Conforms to IS 8623-1 & 3, IEC 61439-1 & 3
- > Suitable for Surface and Flush mounting
- > Available in CRCA sheet steel, RAL9003, powder coated
- > Loose Metal Plugs & Sockets conforms to IS 8804; available in Single Phase & Three Phase



**Metal Plug & Socket**



**Plastic Plug & Socket**

Description	No. of Pins	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
<b>Metal Plug &amp; Sockets</b>				
10 A, 2 Pin + SC <sup>^</sup>	P + N	1	DEMPS110SD	2050
20 A, 2 Pin + SC <sup>^</sup>	P + N	1	DEMPS120SD	2205
20 A, 2 Pin + SC <sup>^</sup>	P + N	2	DEMPS220SD	2390
20 A, 3 Pin + SC <sup>^</sup>	3P	3	DEMPS320SD	4050
32 A, 3 Pin + SC <sup>^</sup>	3P	3	DEMPS332SD	4795
32 A, 3 Pin + SC <sup>^</sup>	3P	4	DEMPS432SD	5100
63 A, 5 Pin + SC <sup>^</sup>	3P+N+E	4	DEMPS463SD	17280
<b>Plastic Plug &amp; Sockets</b>				
16 A, 3 Pin	P+N+E	2	DEPPS316SD	3355
32 A, 3 Pin	P+N+E	4	DEPPS332SD	3620
32 A, 5 Pin	3P+N+E	8	DEPPS532SD	6045
63 A, 5 Pin	3P+N+E	8	DEPPS563SD	15145

**Metal Plug [8536]**



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC <sup>^</sup>	P + N	MPS210P	200
20 A, 2 Pin + SC <sup>^</sup>	P + N	MPS220P	210
20 A, 3 Pin + SC <sup>^</sup>	3P	MPS320P	275
32 A, 3 Pin + SC <sup>^</sup>	3P	MPS332P	525

**Note:** Standard pack quantity - 20 nos.

**Metal Socket [8536]**



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC <sup>^</sup>	P + N	MPS210S	205
20 A, 2 Pin + SC <sup>^</sup>	P + N	MPS220S	225
20 A, 3 Pin + SC <sup>^</sup>	3P	MPS320S	310
32 A, 3 Pin + SC <sup>^</sup>	3P	MPS332S	525

<sup>^</sup> SC-Scraping Earth

**Note:** Standard pack quantity - 20 nos.

For ordering old DBs, replace Cat no with "DB" instead of "DE".  
Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

**New** DBs with provision for TV / Telephone splitters [8537]

**Highlights**

- › Distribution Boards equipped with provisions to mount TV / Telephone splitters
- › Available in SPN & TPN DBs



DB Type	Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
		Incomer + Outgoing			
<b>IP 43 - Metal Door</b>					
SPN	6 way	2	4	DESPN006DDTV	4615
	8 way	2	6	DESPN008DDTV	4960
	12 way	2	10	DESPN012DDTV	6105
	16 way	2	14	DESPN016DDTV	7080
	18 way	2	16	DESPN018DDTV	8375
TPN	4 way	8	4+4+4	DETPN004DDTV	9070
	6 way	8	6+6+6	DETPN006DDTV	10475
	8 way	8	8+8+8	DETPN008DDTV	12490

**Cable End Boxes [8537]**

**Highlights**

- › Available in CRCA sheet steel, RAL9003, powder coated
- › Can be either at the top or bottom of the distribution board

Description	Cat. Nos.	M.R.P. (₹) Per Unit
<b>CEB for SPN DBs</b>		
CEB-SPN Double Door, 4 way	DESPN004CBS	905
CEB-SPN Double Door, 6 way	DESPN006CBS	975
CEB-SPN Double Door, 8 way	DESPN008CBS	1090
CEB-SPN Double Door, 12 way	DESPN012CBS	1215
CEB-SPN Double Door, 16 way	DESPN016CBS	1710
CEB-SPN Double Door, 18 way	DESPN018CBS	1765
<b>CEB for TPN DBs</b>		
CEB-TPE Double Door, 4 way	DETPN004CBS	1170
CEB-TPE Double Door, 6 way	DETPN006CBS	1670
CEB-TPN Double Door, 4 way	DETPN004CBS	1225
CEB-TPN Double Door, 6 way	DETPN006CBS	1720
CEB-TPN Double Door, 8 way	DETPN008CBS	2165
CEB-TPN Double Door, 12 way	DETPN012CBS	3595
CEB-TPN Double Door, 16 way	DETPN016CBS	3630
<b>CEB for Horizontal PPI DBs</b>		
CEB-Horz. PPI Double Door, 4 way	DEHPI004CB	1815
CEB-Horz. PPI Double Door, 6 way	DEHPI006CB	2265
CEB-Horz. PPI Double Door, 8 way	DEHPI008CB	2840
CEB-Horz. PPI Double Door, 12 way	DEHPI012CB	3565
CEB-Horz. PPI Double Door, 16 way	DEHPI016CB	3875
<b>CEB for VTPN DBs</b>		
CEB-VTPN Double Door, Modular Incomer	DEVTMXXXCB	1215
CEB-VTPN Double Door, MCCB Incomer	DEVTXXXCB	4285
<b>CEB for Phase Segregated DBs</b>		
CEB-PSG Double Door, 4 way	DEPSG004CB	3180
CEB-PSG Double Door, 6 way	DEPSG006CB	3790
CEB-PSG Double Door, 8 way	DEPSG008CB	4185
CEB-PSG Double Door, 12 way	DEPSG012CB	4660

**DB Accessories**

**Busbar - Fork Type [8538]**

**Highlights**

- › Available in Single Pole, Double Pole, Three Pole and Four Pole versions
- › Material : Copper



Description	Cat. Nos..	M.R.P. (₹) Per Unit	Std. Pack Qty.
SP 13 Mod	BSP13	405	5
SP 56 Mod	BSP56	1655	5
DP 12 Mod	BDP12	720	5
TP 12 Mod	BTP12	775	5
FP 12 Mod	BFP12	1535	5
End Caps for SP	ECP01	25	10
End Caps for DP/TP	ECP03	55	10
End Caps for FP	ECP04	90	10



**Blanking Plates [8538]**

**Highlights**

- › Available in One module and Half module

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std.Pack Qty.
One Module	BKP10	25	10
Half Module	BKP05	25	10



PDK02

**Padlock [8301]**

**Highlights**

- › Version with standard lock and a common key

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std. Pack Qty.
Lock and Key Kit	PDK02	705	5

For ordering old DBs, replace Cat no with "DB" instead of "DE".  
Eg. - New DB Cat no for SPN 12W DD - DESPN012DDDS, Old DB Cat no for same will be DBSPN012DDDS. Old DBs are available till stock last.

## General Terms

All prices are on Maximum retail price basis inclusive of all duties, GST & any other tax as applicable.

## Warranty Policy

All products listed in the price list are covered by a warranty against manufacturing defects for a period of 18+ months from the date of purchase. For Lauritz Knudsen MCBs & Isolators mounted inside Lauritz Knudsen Distribution Boards, an extended warranty of 5 years is provided.

In the event of a defect due to faulty workmanship or other associated reasons, we will, at our discretion, remedy the defect or replace the faulty parts or the entire product as soon as possible, free of cost.

However, the warranty is subject to proper usage, efficient maintenance, and does not cover defects arising from fire, accidents, inefficient maintenance, faulty operation, or deliberate or accidental damage. It also does not cover damage to power electronic components such as thyristors & IGBTs, which primarily fail due to overtemperature & over-voltage. Users need to take adequate precautions to eliminate these conditions. Manufacturer shall not be responsible & liable for any special, incidental, social or consequential (including lost profits) loss, consequential damages, injury or damages (punitive) of any kind solely attributable to defect or failure of its products. Manufacturer shall not be liable in any manner for the issue of or failure in the performance of other equipment the product is attached to.

Note: We are committed to maintaining our product warranty in line with our standard terms for both the Lauritz Knudsen Brand and the L&T Switchgear brand. The change in brand will not alter our standard warranty terms or any applicable extended warranty terms.

Furthermore, we will ensure that spares and after-sales support remain available throughout the entire product life cycle, regardless of whether the products are under the L&T Switchgear brand or the Lauritz Knudsen Brand

## Comprehensive Service Support

Lauritz Knudsen Electrical & Automation has over seven decades of experience in providing after sales service for low voltage distribution system in every type of industry & commercial complex in India

Lauritz Knudsen Electrical & Automation offers the following services, partnering you in your maintenance of low voltage distribution products:

- › Regular Maintenance
- › Preventive Maintenance Programme
- › On Call
- › Annual Maintenance Contract
- › Product Support for Managing Obsolescence-

# Switchgear Training Centres



## Pune

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
T-156 / 157, MIDC,  
Bhosari, Pune - 411 026  
Tel: 020-2712 0037 / 2712 0653  
E-mail: STC-PUNE@LK-EA.com



## Lucknow

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
C-6 & 7, UPSIDC,  
P. O. Sarojininagar,  
Lucknow - 226 008  
Tel: 97944 54455  
E-mail: STC-LUCKNOW@LK-EA.com



## Delhi

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
A-25, Imperia Complex, First Floor  
Mohan Cooperative Industrial Estate  
Near Sarita Vihar / Mohan Estate Metro Station  
Main Mathura Road, New Delhi - 110044  
Tel: 9899020306 / 9720186726 / 9560845094  
E-mail: STC-DELHI@LK-EA.com



## Kolkata

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre,  
2nd Floor, Block BN3, Sector V,  
Salt Lake City,  
Kolkata - 700091, West Bengal  
Tel: 7738717893 / 7797795567  
E-mail: STC-KOLKATA@LK-EA.com



## Vadodara

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
Behind L&T Knowledge City,  
Near Village Ankhol,  
Vadodara - 390019  
Tel: 0265 6147805 / 6147808  
E-mail: STC-VADODARA@LK-EA.com



## Coonor

Lauritz Knudsen Electrical & Automation  
Switchgear Training Centre  
Ooty-Coonor Main Road  
Yellanahalli P.O.,  
The Nilgiris - 643 243  
Tel: 0423 251 7107  
E-mail: STC-COONOOR@LK-EA.com

# Electrical Standard Products (ESP) Offices

## HEAD OFFICE

Lauritz Knudsen Electrical & Automation, A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra.

Tel: 022-6722 6300 | Fax: 022-6705 1112 | e-mail: CIC@LK-EA.com

## BRANCH OFFICES

Lauritz Knudsen Electrical & Automation  
C-201, The First Commercial Complex,  
B/S Keshavbaug Party Plot, Vastrapur,  
**Ahmedabad - 380 015**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Shri Daneshwari, 1st Floor,  
Plot No. 17, 2nd Cross, Near Old Income  
Tax Office Road, Vidyanagar,  
**Hubballi - 580 021**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
No.10, Fortuna Towers, 2nd Floor,  
Rana Pratap Marg, Near NBRI,  
**Lucknow - 226 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
A06/A07, Second Floor,  
Grand Chandra Complex, Frazer Road  
**Patna - 800 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Wewok Central, #36 Infantry Road,  
**Bengaluru - 560 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
AWFIS Space Solutions, Prestige Phoenix,  
4th floor, 1405, Umanagar, Begumpet,  
**Hyderabad - 500 016**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
El Dorado Building, 3rd Floor, 6,  
Venkatraman Street, Chinna Chokkikulam,  
**Madurai - 625 002**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
UrbanWrk, 5th Floor, Sai Radhe,  
Raja Bahadur Mill Road, Behind Hotel  
Grand Sheraton, Sangamwadi  
**Pune - 411 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Workloop Unit-612, 6th Floor,  
Esplanade One, Rasulgarh,  
**Bhubaneswar, Odisha-751010**  
Phone No: 022 6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Workie, 214 - 2nd Floor,  
Apollo Premier, PU-4,  
Scheme No. 54, Vijay Nagar Square,  
**Indore - 452 010**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Bestech Business Park,  
Tower - A, 2nd floor, Sector - 66  
**Mohali - 160059**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Office No. 211 & 212, Pithalia Plaza,  
KK Road, Near Fafadih Chowk,  
**Raipur - 492 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation,  
The Executive Centre  
Level 8, Olympia Teknos Park  
28, SIDCO Industrial Estate, Guindy,  
**Chennai - 600 032**, Tamil Nadu,  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Office No. 430, 4th Floor,  
Jaipur Electronic Market, Riddhi Siddhi,  
Gopalpura Bypass,  
**Jaipur - 302 018**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
TC II, Tower B, PRIMA BAY Gate No. 5,  
Saki Vihar Road Powai,  
**Mumbai - 400 072**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation,  
DevX 4th Floor, A Wing, Om 9 Square,  
150 Ft Ring Road, Near Nana Mava Circle,  
Opp Silver Heights,  
**Rajkot - 360 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Playworkz Coworking Space  
43 & 44, 3rd Cross,  
Bharathy Colony, Peelamedu,  
**Coimbatore - 641 004**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
GDR Siddha, Ground Floor, N Road  
Bistupur, Opposite St. Mary's Church,  
**Jamshedpur - 831 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Unnati Building, 2nd Floor,  
Automation Campus, A-600, TTC Industrial  
Area Shil-Mahape Road, Mahape,  
**Navi Mumbai - 400 710**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
10th Floor, Titaanium Business,  
Bhimrad Road, Althan  
**Surat - 395 017**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
3rd Floor, 1&2 Vijay Park,  
Main Chakrata Road, Opp. Anandam,  
Near Ballapur chowk,  
**Dehradun - 248 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Business Communication Centre  
2nd Floor, Chiramel Chambers,  
Kurisupally Road, Ravipuram,  
**Kochi - 682 015**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
M1 & M2, Mezzanine Floor,  
Himalaya Excellency,  
Plot No. C-47, Pratap Nagar Square,  
**Nagpur - 440 022**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
11th Floor, Block-D, Notus IT Park,  
Sarabhai Campus, Bhailal Amin Marg,  
**Vadodara - 390 023**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Ground Floor, B-27,  
Biplab Rashbihari Sarani,  
Sector 2A, Bidhan Nagar,  
**Durgapur - 713 212**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz & Knudsen Electrical & Automation,  
207, 2nd floor, Revolution Complex,  
Station Road, E Ward,  
Next to Pedestrian Bridge,  
**Kolhapur - 416 001**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation,  
3rd floor, Uttam Tower by Viraj Estate,  
Sharanpur Road,  
**Nasik - 422 002**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
Naga Chambers, 3rd Floor, D/No. 12-1-16,  
Plot No. 49, Survey No. 1051, Waltair Main Road,  
**Visakhapatnam - 530 002**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
6th Floor, Exotica Greens, A Block, 191,  
R G Baruah Road, Guwahati Central,  
**Guwahati - 781 005**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
2nd Floor, BN3, Salt Lake, Sector-V,  
**Kolkata - 700 091**  
Phone No: 022-6932 7800  
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation  
A-25, 1st Floor, Imperia Complex,  
Mohan Corporative Industrial Estate,  
Near Sarita Vihar Metro Station,  
Mathura Road,  
**New Delhi - 110 044**  
Phone no: 022-6932 7800  
e-mail: CIC@LK-EA.com

Product improvement is a continuous process. For the latest information and special application, please contact any of our offices listed here. Product photographs shown for representative purpose only.



### Lauritz Knudsen Electrical & Automation, Electrical Standard Product

A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra, Phone No: 022-6722 6300 | Web: www.LK-EA.com

### Customer Interaction Center (CIC)

Phone no: 022-6932 7800

Web: www.LK-EA.com | e-mail: CIC@LK-EA.com